

Product Specifications for Ti25 and Ti10:

	Fluke Ti25	Fluke Ti10
Imaging performance		
Thermal: Field of View (FOV)	23° horizontal x 17° vertical	
Minimum focus distance	Thermal lens: 15 cm (approx. 6 in), Visible (visual) light lens: 46 cm (approx. 18 in)	
Thermal sensitivity (NETD)	<0.1 °C at 30 °C (100 mK)	<0.2 °C at 30 °C (200 mK)
Minimum span (Auto/Manual)	5 °C/2.5 °C	10 °C/5 °C
Focus	Manual	
Detector size	160 x 120	
Visual: On camera operating modes	Picture-in-Picture (Blending is user selectable between MAX, MED and MIN) and full screen IR (Blending is user selectable between MAX, MED and MIN)	Full Picture-in-Picture and full screen IR
Visual (Visible light) camera	640 x 480 pixels, full color	
Temperature measurement		
Temperature range	-20 °C to +350 °C (-4 °F to +662 °F), 2 ranges	-20 °C to +250 °C (-4 °F to +482 °F)
Accuracy	± 2 °C or 2 % (whichever is greater)	± 5 °C or 5 % (whichever is greater)
Measurement modes	Center point and hot and cold markers	Center point
On-screen emissivity correction	Yes	No
Image presentation		
Digital display	9.1 cm (3.6 in) diagonal landscape color VGA (640 x 480) LCD	
LCD backlight	Selectable bright or auto	
Palettes	Ironbow, blue-red, high contrast, amber, hot metal, grey	Ironbow, blue-red, high contrast, grey
Image and data storage		
Fully radiometric	Yes	
Storage medium	2GB SD card stores up to 3000 .bmp IR images or 1200 .IS2 IR-Fusion images	
File formats supported	Exportable to JPEG, BMP, GIF, PNG, TIFF, WMF EXIF, and EMF	
Voice memo recorder (voice annotation)	Yes	No
Software Controls and adjustments		
	SmartView ; Full analysis and reporting software included	
Set-up controls	Date/time, °C/°F, language, emissivity, hot spot and cold spot on image	Date/time, °C/°F, language
Language selection	English, German, French, Spanish, Portuguese, Italian, Swedish, Finnish, Russian, Czech, Polish, Turkish, Simplified Chinese, Traditional Chinese, Korean, Japanese	
Image controls	Smooth auto scaling and manual scaling	
On-screen indicators	Battery status, real time clock and center point temperature, range and span indication and high and low alarm settings	
Power		
Battery type	Internal rechargeable battery (included)	
Battery operating time	3 to 4 hours continuous operation	
Battery charging	2 hours with ac charger or dc car charger (charges battery while operating)	
AC operation	AC adapter/charger 110/230 V ac, 50/60 Hz	
Power saving	Automatic shutdown and sleep modes (user specified)	
Environmental and mechanical design		
Operating temperature	-10 °C to +50 °C (+14 °F to +122 °F)	
Storage temperature	-20 °C to +50 °C (-4 °F to +122 °F)	
Relative humidity	Operating and storage 10 % to 90 %, non-condensing	
Water and dust resistant	IP54	
Two meter (6.6 feet) drop test	Yes	
Protective lens cover	Yes	
Weight (including battery)	1.2 kg (2.6 lbs)	

Imager size (HxWxD)	267 mm x 127 mm x 152 mm (10.5 in x 5.0 in x 6.0 in)
Other	
Warranty	Two-years
EN 61010-1 2nd edition and EN61326-1	Yes